

PLAFONIERA LED



LED CEILING LAMP
LED DECKENLEUCHTEN
СВЕТИЛЬНИК LED
PLAFONIÉRA LED


SLS, SLR TALAR



SLR




SLS



[mm] **a**

SLR-120: Ø 115
SLR-180: Ø 168
SLR-240: Ø 217
SLR-300: Ø 295



[mm] **b**

SLS-120: 115x115
SLS-180: 168x168
SLS-240: 217x217
SLS-300: 295x295

MATERIAL ► stop aluminium, klosz: PMMA
MATERIAL ► aluminum alloy, lamp cover: PMMA
MATERIAL ► aluminiumlegierung, schirm: PMMA
МАТЕРИАЛ ► алюминиевый сплав, колпак: PMMA
MATERIAL ► hliník, stínidlo: PMMA

- 230V 50Hz
- PF >0,5
- 3000K 4000K
- CRI Ra ≥ 80
- 120°
- 30000h
- 30000x
- IK 02
- 35°C
5°C
- IP 20


SAMSUNG LED inside



biała obudowa z mlecznym kloszem



solidna konstrukcja



otwory wspomagające chłodzenie oprawy



zewnętrzny zasilacz w komplecie



szybkolączka zasilacza ułatwiająca montaż



kod

C39-SLS-120-060-3K
C39-SLS-120-060-4K
C39-SLS-180-120-3K
C39-SLS-180-120-4K
C39-SLS-240-180-3K
C39-SLS-240-180-4K
C39-SLS-300-240-3K
C39-SLS-300-240-4K
C39-SLR-120-060-3K
C39-SLR-120-060-4K
C39-SLR-180-120-3K
C39-SLR-180-120-4K
C39-SLR-240-180-3K
C39-SLR-240-180-4K
C39-SLR-300-240-3K
C39-SLR-300-240-4K



EAN

5900280909855
5900280909862
5900280909879
5900280909886
5900280909893
5900280909909
5900280914644
5900280914699
5900280909794
5900280909800
5900280909817
5900280909824
5900280909831
5900280909848
5900280914644
5900280914651



opakowanie

1/20
1/20
1/20
1/20
1/10
1/10
1/10
1/10
1/20
1/20
1/10
1/10
1/10
1/10
1/20
1/20



barwa światła [K]

3000
4000
3000
4000
3000
4000
3000
4000
3000
4000
3000
4000
3000
4000
3000
4000

P_{ON}

moc w trybie włączenia [W]

6
6
12
12
18
18
24
24
6
6
12
12
18
18
24
24



strumień świetlny [lm]

540
570
1080
1140
1620
1710
2050
2150
540
570
1080
1140
1620
1710
2050
2150